

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/55 - 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	153 A8/149 B
<b>LI/SS FREE ROLLING</b>	165 A8/161 B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94006434	<b>RC (IN)</b>	158.1
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	53.3	<b>ECE</b>	E4-106R-002277
<b>SLR (IN)</b>	22.9	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	26	29
<b>5 FR</b>	13430	14940	15890
<b>10 FR</b>	12080	13450	14310
<b>20 FR</b>	10740	11950	12720
<b>25 FR</b>	9590	10670	11350
<b>30 FR</b>	8630	9600	10200
<b>5 DW</b>	9520	10580	11260
<b>10 DW</b>	8560	9520	10140
<b>20 DW</b>	7620	8470	9020
<b>25 DW</b>	6800	7560	8050
<b>30 DW</b>	6120	6800	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.