


# AGRIMAX V- FLECTO

**VF 600/70 R 30**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	168 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94064601	<b>RC (IN)</b>	185.5
<b>SW (IN)</b>	23.7	<b>RIM REC</b>	DW 21 B
<b>OD (IN)</b>	63.1	<b>RIM ALT</b>	DW 20 B
<b>SLR (IN)</b>	27.6	<b>ECE</b>	E11-106R-006162

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	5610	6500	7410	8420	9310	10220	11230
<b>FROM 40 TO 25</b>	6170	7150	8150	9260	10240	11230	12350
20	6290	7290	8300	9440	10440	11450	12590
12	6420	7430	8470	9620	10650	11670	12830
5	6790	7860	8950	10180	11250	12350	13580
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	8640	10010	11400	12960	14330	15720	17280
5 HT	6290	7290	8300	9440	10440	11450	12590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.