


MULTIMAX MP 522

TYRE SIZE	280/80 R 18 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	132 A8/B



DIMENSIONS US STANDARD

USA CODE	94045044	RC (IN)	108.2
SW (IN)	11.1	RIM REC	W 9; 9; 9 SDC
OD (IN)	35.7	RIM ALT	W 8; W 10
SLR (IN)	16.6	ECE	E11-106R-002962

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	2120	2510	2870	3260	3660	3920	4410	-	-
25	2120	2510	2870	3260	3660	3920	4410	-	-
20	2270	2690	3080	3490	3920	4200	4720	-	-
15	2360	2800	3190	3630	4070	4360	4890	-	-
5 CYC.	2580	3170	3740	4300	4890	5320	6020	6350	6610
STATIC	3960	4870	5730	6590	7510	8170	9240	9740	10140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.