


FLOTATION 648

TIRE SIZE	850/50 - 30.5
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	HD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	176 A8/173 B
LI/SS FREE ROLLING	189 A8/185 B



DIMENSIONES US STANDARD

CÓDIGO USA	94030286	RC (IN)	194.3
SW (IN)	33.5	RIM REC	AG 28.00
OD (IN)	65.0	ECE	E11-106R-004566
SLR (IN)	28.0	PR	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33	34	36
5 FR	30280	31030	31790
10 FR	27250	27930	28610
20 FR	24220	24820	25430
25 FR	21630	22170	22710
30 FR	19470	19950	20390
5 DW	20870	21380	21910
10 DW	18780	19250	19720
20 DW	16690	17110	17530
25 DW	14900	15280	15650
30 DW	13410	13750	14330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.