


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>600/65 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 D ; 160 A8



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94062638	<b>RC (IN)</b>	195.3
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	64.7	<b>RIM ALT</b>	W 18 L
<b>SLR (IN)</b>	29.2	<b>ECE</b>	E4-106R-001405

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	4360	5090	5730	6370	7010	7550	8370	9100
30	4600	5360	6030	6690	7360	7940	8800	9560
25	4760	5560	6250	6940	7640	8230	9130	9920
20	5030	5860	6590	7330	8060	8690	9630	10460
5 LT	5850	6830	7680	8540	9390	10120	11220	12190
5 HT	5030	5860	6590	7330	8060	8690	9630	10460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.