

# AW 708

<b>TIRE SIZE</b>	<b>19.0/45 - 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	144 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94010240	<b>RC (IN)</b>	99.8
<b>SW (IN)</b>	18.5	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	34.1	<b>ECE</b>	E4-106R-001883
<b>SLR (IN)</b>	15.0	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	8640
15 FR	7340
20 FR	6910
25 FR	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.