

# FLOTATION TR 675

<b>TIRE SIZE</b>	<b>500/60 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	IMPLEMENTOS AGRÍCOLAS / REBOQUE / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	DUAL BEAD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	155 A8/151 B
<b>LI/SS FREE ROLLING</b>	168 A8/164 B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94050147	<b>RC (IN)</b>	141.9
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	46.5	<b>RIM ALT</b>	15.00; 17.00
<b>SLR (IN)</b>	21.3	<b>ECE</b>	E11-106R-004395

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54	55	58
<b>5 FR</b>	16370	16630	17280
<b>10 FR</b>	14740	14970	15550
<b>20 FR</b>	13090	13300	13820
<b>25 FR</b>	11690	11880	12350
<b>30 FR</b>	10530	10690	11020
<b>5 DW</b>	11580	11770	11960
<b>10 DW</b>	10430	10590	10770
<b>20 DW</b>	9270	9420	9570
<b>25 DW</b>	8280	8410	8540
<b>30 DW</b>	7450	7570	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.