


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/60 R 46
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	174 D



ABMESSUNGEN US STANDARD

USA-CODE	94514182	RC (IN)	239.8
SW (IN)	28.1	RIM REC	DW 25 B
OD (IN)	80.4	RIM ALT	DW 27 B
SLR (IN)	35.3	ECE	E11-106R-0011234

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	14	17	20	23
45	7400	8610	9820	11030	12250	13450
FROM 40 TO 25	8120	9460	10790	12110	13450	14770
20	8290	9640	11000	12360	13710	15070
12	8450	9840	11220	12610	13990	15370
5	8940	10410	11870	13330	14790	16250
UPTO 20 CYC	9230	10740	12250	13760	15270	16770
UPTO 10 CYC	11010	12820	14620	16420	18220	20020
UPTO 5CYC	12070	14040	16020	17990	19960	21930
5 HT	8290	9640	11000	12360	13710	15070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.