


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>460/65 R 24 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 D ; 156 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94058655	<b>RC (IN)</b>	143.5
<b>SW (IN)</b>	17.9	<b>RIM REC</b>	DW 14 L
<b>OD (IN)</b>	47.8	<b>RIM ALT</b>	DW 15 L ; DW 13
<b>SLR (IN)</b>	21.6	<b>ECE</b>	E11-106R-005109

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58
40	3040	3730	4190	4950	5630	6320	6920	7610
30	3280	4030	4520	5350	6080	6820	7480	8220
25	3530	4320	4850	5730	6530	7320	8020	8820
20	3650	4480	5020	5930	6760	7570	8300	9130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.