


# MULTIMAX MP 513

<b>TIRE SIZE</b>	<b>375/70 R 20 MPT</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	UNIVERSELLES FAHRZEUG / DÜNGER-FAHRZEUG / UNIVERSELLES FAHRZEUG
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	136 G



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94051847	<b>RC (IN)</b>	122.9
<b>SW (IN)</b>	14.8	<b>RIM REC</b>	12
<b>OD (IN)</b>	40.7	<b>RIM ALT</b>	W 10; DW 10; 11; 11 SDC; W 11; DW 11; 12 SDC
<b>SLR (IN)</b>	18.6	<b>ECE</b>	E11-54R-0016139

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	36	44	51
55	2670	3160	3760	4350	4940
40	2900	3440	4090	4730	5370
25	3080	3650	4330	5020	5690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.