


# MULTIMAX MP 527

<b>TYRE SIZE</b>	<b>440/80 R 28 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	156 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	441	<b>RIM REC</b>	DW 14 L
<b>OD (MM)</b>	1415	<b>RIM ALT</b>	DW 13 ; DW 13 L ; DW 15 L
<b>SLR (MM)</b>	648	<b>ECE</b>	E11-106R-002984
<b>RC (MM)</b>	4270	<b>SRI</b>	675

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.6	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
50	2300	2725	2940	3150	3360	3575	3790	4000	-	-
40	2300	2725	2940	3150	3360	3575	3790	4000	-	-
30	2480	2930	3155	3380	3605	3830	4055	4280	-	-
25	2570	3040	3270	3505	3740	3970	4205	4440	-	-
10 CYC.	2840	3470	3790	4105	4420	4735	5050	5370	5685	6000
STATIC	4360	5330	5810	6295	6780	7265	7750	8230	8715	9200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.