


# AGRIMAX SPARGO SB

<b>TIRE SIZE</b>	<b>VF 380/90 R 54</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR / BESPRUTNINGSBIL
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	176 D



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	395	<b>RIM REC</b>	W13
<b>OD (MM)</b>	2060	<b>RIM ALT</b>	W12;DW12;W13A; DW13;DW13A
<b>SLR (MM)</b>	957	<b>ECE</b>	E11-106R-0010178
<b>RC (MM)</b>	6310	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
<b>70</b>	2780	3105	3495	3815	4010	4205	4335	4465	4690	4915	5110	5305	5465	5625	5790	5950	6210	6465
<b>FROM 65 TO 40</b>	3055	3410	3835	4190	4405	4615	4760	4900	5150	5400	5610	5825	6000	6180	6355	6535	6820	7100
<b>30</b>	3120	3480	3915	4275	4495	4710	4855	5000	5255	5510	5725	5945	6125	6305	6485	6670	6960	7245
<b>20</b>	3180	3545	3990	4360	4580	4805	4950	5100	5355	5615	5835	6060	6245	6425	6610	6795	7090	7385
<b>10</b>	3360	3750	4220	4610	4845	5080	5235	5390	5665	5940	6170	6405	6600	6795	6990	7190	7500	7810
<b>UPTO 30 CYC</b>	3470	3870	4355	4760	5000	5240	5405	5565	5845	6130	6370	6610	6815	7015	7215	7420	7740	8060
<b>UPTO 15 CYC</b>	4140	4620	5200	5680	5970	6260	6450	6645	6980	7315	7605	7895	8135	8375	8615	8855	9240	9625
<b>UPTO 10 CYC</b>	4535	5065	5695	6225	6540	6855	7070	7280	7650	8015	8335	8650	8915	9175	9440	9705	10125	10545
<b>10 HT</b>	3120	3480	3915	4275	4495	4710	4855	5000	5255	5510	5725	5945	6125	6305	6485	6670	6960	7245

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.