


# AW 705

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>16.0/70 - 20</b>  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS       |
| <b>MACHINERY</b>          | PRESSE À PAILLE / OUTILLAGE<br>AGRICOLE / REMORQUE /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 156 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                    |
|-----------------|------|----------------|--------------------|
| <b>SW (MM)</b>  | 408  | <b>RIM REC</b> | 13.0               |
| <b>OD (MM)</b>  | 1075 | <b>RIM ALT</b> | 12 SDC; 13 SDC; 14 |
| <b>SLR (MM)</b> | 480  | <b>ECE</b>     | E4-106R-002267     |
| <b>RC (MM)</b>  | 3155 | <b>PR</b>      | 16                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 |
|------------|------|
| 10 FR      | 5600 |
| 25 FR      | 4760 |
| 30 FR      | 4480 |
| 40 FR      | 4000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.