


AGRIMAX SPARGO

TIRE SIZE	VF 380/90 R 46 CFO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	175 D



DIMENSIONI US STANDARD

CODICE USA	94518494	RC (IN)	220.9
SW (IN)	15.4	RIM REC	DW 13 A
OD (IN)	72.9	RIM ALT	W 13 A ; DW 12
SLR (IN)	33.4	ECE	E11-106R-007527-01

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64	67
45	6250	7040	7690	8080	8470	8730	9000	9520	9910	10300	10700	11080	11350	11730	12000	12520	13040	13690
FROM 40 TO 25	6880	7740	8460	8890	9320	9610	9890	10470	10900	11330	11750	12180	12470	12900	13190	13760	14330	15220
20	7020	7900	8620	9070	9500	9790	10080	10660	11100	11550	11990	12430	12710	13150	13440	14030	14620	15520
12	7150	8050	8790	9240	9680	9980	10280	10870	11330	11780	12220	12670	12970	13410	13710	14300	14910	15830
5*	7570	8510	9300	9770	10240	10560	10870	11500	11980	12450	12920	13400	13720	14190	14500	15130	15770	16740
UPTO 10 CYC.	9330	10500	11470	12050	12640	13020	13410	14180	14760	15350	15930	16520	16900	17490	17870	18660	19430	20620
UPTO 20 CYC.	7820	8800	9610	10100	10590	10920	11240	11890	12370	12870	13350	13840	14170	14650	14980	15630	16290	17280

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.