

TR 463



TR 463



TR 463 has been specially designed for backhoe loaders and industrial tractors. Made of a superior tread compound and featuring a strong nylon casing, this tire stands for best results in industrial and OTR applications, and on construction sites. TR 463 provides excellent traction for drive wheels.



	SIZE	TT/TL	PR	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
					REC RIM	ALT RIM					
											
Ø24"	16.9 - 24	TL	14	152 A8	DW 15 L	DW 14 L		1300	584	3877	IND
	16.9 - 24	TL	12	149 A8	DW 15 L	DW 14 L		1300	584	3877	IND
Ø26"	18.4 - 26	TL	14	158 A8	DW 16 L	DW 15 L		1425	637	4215	IND
	18.4 - 26	TL	12	156 A8	DW 16 L	DW 15 L		1425	637	4215	IND
Ø28"	16.9 - 28	TL	12	152 A8	DW 15 L	DW 14 L		1405	636	4190	IND

IND: INDUSTRIAL

TECHNOLOGIES		PERFORMANCES	
	 R4		Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index
	 158 kg		

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baikrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026