

AS 504

| | |
|---------------------------|---------------------------------------------------------------------------------------------------|
| TIRE SIZE | 7.5L - 15 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 100 A8 |
| LI/SS FREE ROLLING | 113 A8 |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 210 | RIM REC | 6 LB |
| OD (MM) | 765 | RIM ALT | 5 K; 5½ J; 5½ K |
| SLR (MM) | 354 | ECE | E4-106R-002632 |
| RC (MM) | 2280 | PR | 8 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.70 |
|------------|------|
| 10 FR | 1610 |
| 25 FR | 1370 |
| 30 FR | 1290 |
| 40 FR | 1150 |
| 10 DW | 1120 |
| 25 DW | 950 |
| 30 DW | 895 |
| 40 DW | 800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.