


AGRIMAX RT 657

| | |
|---------------------|--|
| TYRE SIZE | 480/65 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 142 D ; 145 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 479 | RIM REC | W 15 L |
| OD (MM) | 1335 | RIM ALT | W 14 L |
| SLR (MM) | 610 | ECE | E4-106R-000653 |
| RC (MM) | 4091 | SRI | 650 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 1275 | 1485 | 1670 | 1855 | 2045 | 2200 | 2440 | 2650 |
| 50 | 1340 | 1560 | 1755 | 1950 | 2145 | 2315 | 2565 | 2785 |
| 40 | 1395 | 1625 | 1830 | 2030 | 2235 | 2410 | 2670 | 2900 |
| 30 | 1465 | 1710 | 1925 | 2135 | 2350 | 2535 | 2810 | 3050 |
| 10 LT | 1710 | 1995 | 2240 | 2490 | 2740 | 2955 | 3275 | 3555 |
| 10 HT | 1465 | 1710 | 1925 | 2135 | 2350 | 2535 | 2810 | 3050 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.