


AW 909

| | |
|---------------------------|--|
| TIRE SIZE | 10.0/80 - 12 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 121 A8 |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94010547 | RC (IN) | 81.9 |
| SW (IN) | 10.4 | RIM REC | 9.00 |
| OD (IN) | 28.0 | RIM ALT | 7.0 |
| SLR (IN) | 12.3 | ECE | E4-106R-002662 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 57 |
|-----------|------|
| 5 FR | 4480 |
| 15 FR | 3800 |
| 20 FR | 3580 |
| 25 FR | 3200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.