


AGRIMAX RT 765

TIRE SIZE	600/70 R 30
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	152 D



DIMENSIUNI IS STANDARD

SW (MM)	611	RIM REC	DW 20 B
OD (MM)	1602	RIM ALT	DW 18 L; W 18 L
SLR (MM)	711	ECE	E11-106R-005523
RC (MM)	4774	SRI	750

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	1955	2275	2595	2915	3235	3550
50	2055	2390	2725	3060	3395	3730
40	2140	2490	2840	3190	3540	3890
30	2250	2615	2985	3350	3720	4085
10 LT	2620	3050	3475	3905	4335	4760
10 HT	2250	2615	2985	3350	3720	4085

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.