

AS 504

TIRE SIZE	7.50 - 16
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	92 A8
LI/SS FREE ROLLING	104 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	209	RIM REC	5.50 F
OD (MM)	803	RIM ALT	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F
SLR (MM)	372	PR	6
RC (MM)	2475	SRI	390

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.30
10 FR	1260
25 FR	1070
30 FR	1010
40 FR	900
10 DW	880
25 DW	750
30 DW	705
40 DW	630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.