


AGRIMAX TERIS

| | |
|---------------------|--|
| TIRE SIZE | 650/75 R 32 CHO |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HARVESTER / COTTON PICKER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 172 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA CODE | 94032860 | RC (IN) | 211.7 |
| SW (IN) | 26.4 | RIM REC | DW 21 B |
| OD (IN) | 70.7 | RIM ALT | DW 20 B; DW 23 B |
| SLR (IN) | 32.1 | ECE | E4-106R-001425 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 20 | 23 | 29 | 35 | 41 | 46 |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 6390 | 7360 | 9030 | 9870 | 10840 | 11810 | 12790 | 13890 |
| 25 | 6390 | 7360 | 9030 | 9870 | 10840 | 11810 | 12790 | 13890 |
| 20 | 6840 | 7880 | 9670 | 10560 | 11610 | 12640 | 13690 | 14870 |
| 10 CYC | 10550 | 12150 | 14900 | 16280 | 17880 | 19490 | 21090 | 22920 |
| 5 CYC | 11510 | 13260 | 16260 | 17760 | 19510 | 21250 | 23000 | 25000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.