

AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 320/85 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 143 A8/B |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|------------------------|
| CÓDIGO USA | 94039593 | RC (IN) | 180.3 |
| SW (IN) | 13.0 | RIM REC | W 11 |
| OD (IN) | 59.4 | RIM ALT | W 9; W 10; DW 10; DW11 |
| SLR (IN) | 27.6 | ECE | E4-106R-000781 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 |
|-----------|------|------|------|------|------|------|------|------|------|
| 30 | 2170 | 2520 | 3310 | 4030 | 4390 | 4700 | 5110 | 5530 | 6000 |
| 25 | 2170 | 2520 | 3310 | 4030 | 4390 | 4700 | 5110 | 5530 | 6000 |
| 20 | 2330 | 2710 | 3550 | 4320 | 4710 | 5030 | 5480 | 5930 | 6440 |
| 5 LT | 2910 | 3390 | 4440 | 5400 | 5890 | 6290 | 6860 | 7420 | 8060 |
| 5 HT | 2330 | 2710 | 3550 | 4320 | 4710 | 5030 | 5480 | 5930 | 6440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.