


# FLOTATION 648

<b>TIRE SIZE</b>	<b>700/50 - 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	162 A8/158 B
<b>LI/SS FREE ROLLING</b>	174 A8/170 B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94006526	<b>RC (IN)</b>	161.4
<b>SW (IN)</b>	27.6	<b>RIM REC</b>	24.00
<b>OD (IN)</b>	54.1	<b>ECE</b>	E4-106R-002279
<b>SLR (IN)</b>	24.4	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	29	32	35
<b>5 FR</b>	18580	19640	20680
<b>10 FR</b>	16720	17680	18610
<b>20 FR</b>	14860	15720	16540
<b>25 FR</b>	13270	14030	14770
<b>30 FR</b>	11950	12630	13230
<b>5 DW</b>	13180	13930	14660
<b>10 DW</b>	11860	12540	13190
<b>20 DW</b>	10540	11140	11730
<b>25 DW</b>	9410	9950	10470
<b>30 DW</b>	8480	8960	9370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.