

# TF 9090

|                     |                                   |
|---------------------|-----------------------------------|
| <b>TIRE SIZE</b>    | 7.50 - 18                         |
| <b>UM</b>           | US STANDARD                       |
| <b>CONSTRUCTION</b> |                                   |
| <b>MACHINERY</b>    | SMALL TRACTOR / TRACTOR / TRAILER |
| <b>VERSION</b>      | STANDARD                          |
| <b>TIRE TYPE</b>    | TT                                |
| <b>LI/SS</b>        | 97 A8                             |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94021154 | <b>RC (IN)</b> | 100.9           |
| <b>SW (IN)</b>  | 8.1      | <b>RIM REC</b> | 5.50 F          |
| <b>OD (IN)</b>  | 33.9     | <b>ECE</b>     | E11-106R-004317 |
| <b>SLR (IN)</b> | 15.9     | <b>PR</b>      | 6               |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>44</b> |
| 25               | 1610      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.