


AGRIMAX RT 600

| | |
|---------------------|--|
| TIRE SIZE | 750/70 R 26 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SKÖRDEMASKIN / SPRIDARE / TRAKTOR / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 172 A8/B |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 780 | RIM REC | DW 25 B |
| OD (MM) | 1750 | RIM ALT | DW 24 B |
| SLR (MM) | 785 | ECE | E11-106R-007934 |
| RC (MM) | 5269 | SRI | 825 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 |
|------------|------|------|------|------|------|------|------|------|-------|-------|-------|
| 50 | 2710 | 3150 | 3595 | 4035 | 4475 | 4915 | 5420 | 5735 | 6300 | - | - |
| 40 | 2710 | 3150 | 3595 | 4035 | 4475 | 4915 | 5420 | 5735 | 6300 | - | - |
| 30 | 2905 | 3375 | 3850 | 4320 | 4795 | 5265 | 5805 | 6145 | 6750 | - | - |
| 10 LT | 3635 | 4225 | 4820 | 5410 | 6000 | 6595 | 7270 | 7690 | 8450 | - | - |
| 10 HT | 2905 | 3375 | 3850 | 4320 | 4795 | 5265 | 5805 | 6145 | 6750 | - | - |
| 10 CYC | - | 5065 | 5775 | 6480 | 7190 | 7900 | 8710 | 9215 | 10125 | 10285 | 10710 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.