

AS 504

TIRE SIZE	6.5/80 - 12
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	80 A8
LI/SS FREE ROLLING	93 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019205	RC (IN)	72.3
SW (IN)	6.7	RIM REC	5 J
OD (IN)	23.9	RIM ALT	5 JA
SLR (IN)	11.1	ECE	E4-106R-002180

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	52
5 FR	2010
15 FR	1710
20 FR	1610
25 FR	1430
5 DW	1390
15 DW	1180
20 DW	1110
25 DW	990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.