

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>380/85 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	137 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94033102	<b>RC (IN)</b>	177.3
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	59.4	<b>RIM ALT</b>	W 11; W 13
<b>SLR (IN)</b>	26.9	<b>ECE</b>	E4-106R-000655

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	2790	3250	3700	4170	4620	5080
<b>25</b>	2790	3250	3700	4170	4620	5080
<b>20</b>	3000	3480	3970	4460	4950	5430
<b>5 LT</b>	3750	4350	4970	5580	6190	6800
<b>5 HT</b>	3000	3480	3970	4460	4950	5430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.