

# AS 504

<b>TYRE SIZE</b>	<b>6.5/80 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	72 A8
<b>LI/SS FREE ROLLING</b>	84 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94019199	<b>RC (IN)</b>	72.3
<b>SW (IN)</b>	6.7	<b>RIM REC</b>	5 J
<b>OD (IN)</b>	23.9	<b>RIM ALT</b>	5 JA
<b>SLR (IN)</b>	11.1	<b>ECE</b>	E11-106R-003440

## LOAD CAPACITY (LBS/TYRE)

<b>MPH / PSI</b>	<b>35</b>
<b>5 FR</b>	1540
<b>15 FR</b>	1310
<b>20 FR</b>	1230
<b>25 FR</b>	1100
<b>5 DW</b>	1090
<b>15 DW</b>	930
<b>20 DW</b>	880
<b>25 DW</b>	780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.