


PL 801

| | |
|---------------------|---|
| TIRE SIZE | 7.00 - 15 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ROTOR RAKE/ TEDDER / HAY HARVESTER / FORKLIFT / HARVESTER / IMPLEMENTS / FORKLIFT |
| VERSION | STANDARD |
| TIRE TYPE | TT |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|--------------|
| USA CODE | 94007363 | RIM ALT | 5.50 BD; 5.5 |
| SW (IN) | 8.1 | PR | 14 |
| OD (IN) | 30.5 | | |
| RIM REC | 6.0 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 145 | 150 |
|---------------------------|------|------|
| 15 LOAD WHEEL | 6825 | - |
| 15 STEER WHEEL | 5765 | - |
| 5 OTHER VEHICLES | 5765 | - |
| 15 OTHER VEHICLES | 4235 | - |
| STATIC SIDE LOADER | - | 9315 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.