

# PL 801

<b>TIRE SIZE</b>	<b>8.15 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	РОТОРНЫЕ ГРАБЛИ / СЕНОВОРОШИЛКА / КОМБАЙН / ВИЛОЧНЫЙ ПОГРУЗЧИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ВИЛОЧНЫЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94007257	<b>RIM ALT</b>	7.00 BD
<b>SW (IN)</b>	8.5	<b>PR</b>	12
<b>OD (IN)</b>	28.3		
<b>RIM REC</b>	7.0		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	120
<b>15 LOAD WHEEL</b>	7595
<b>15 STEER WHEEL</b>	5840
<b>5 OTHER VEHICLES</b>	7595
<b>15 OTHER VEHICLES</b>	5840
<b>STATIC SIDE LOADER</b>	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.