

AGRIMAX RT 955

TIRE SIZE	230/95 R 44
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	134 A8/B



РАЗМЕРЫ IS STANDARD

SW (MM)	228	RIM REC	W 7
OD (MM)	1556	RIM ALT	W 8
SLR (MM)	739	ECE	E4-106R-000777
RC (MM)	4788	SRI	750

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	830	1085	1315	1445	1530	1675	1825	1975	2120	-
40	830	1085	1315	1445	1530	1675	1825	1975	2120	-
30	890	1160	1410	1545	1635	1795	1955	2115	2270	-
10	990	1245	1530	1815	2100	2165	2420	2675	2930	3180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.