

# PAC MASTER

|                     |                     |
|---------------------|---------------------|
| <b>TIRE SIZE</b>    | <b>10.5/80 - 16</b> |
| <b>UM</b>           | US STANDARD         |
| <b>CONSTRUCTION</b> | BIAS                |
| <b>MACHINERY</b>    | COMPACTADOR         |
| <b>VERSÃO</b>       | STANDARD            |
| <b>TIRE TYPE</b>    | TL                  |



## DIMENSÕES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94053278 | <b>RC (IN)</b> | 97.6            |
| <b>SW (IN)</b>    | 10.8     | <b>RIM REC</b> | 8.0             |
| <b>OD (IN)</b>    | 31.9     | <b>ECE</b>     | E11-106R-004647 |
| <b>SLR (IN)</b>   | 15.0     | <b>PR</b>      | 14              |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>87</b> |
|------------------|-----------|
| 5                | 6120      |
| 10               | 4960      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.