

FLOTATION 648

TIRE SIZE	550/45 - 22.5
UM	IS STANDARD
CONSTRUCTION	⊗ BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	147 A8/144 B
LI/SS FREE ROLLING	159 A8/156 B



DIMENSÕES IS STANDARD

SW (MM)	525	RIM REC	AG 16.00
OD (MM)	1070	ECE	E4-106R-002309
SLR (MM)	488	PR	16
RC (MM)	3253		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.40	2.60	2.80
10 FR	5600	5865	6125
20 FR	5040	5280	5515
30 FR	4480	4695	4900
40 FR	4000	4190	4375
50 FR	3600	3770	4000
10 DW	3935	4125	4305
20 DW	3540	3710	3875
30 DW	3145	3300	3445
40 DW	2810	2945	3075
50 DW	2530	2650	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.