

# AGRIMAX RT 765

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>380/70 R 24</b>                                                    |
| <b>UM</b>        | US STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / TRACTOR / VINEYARD<br>HARVESTER / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | SPECIAL                                                               |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 125 D                                                                 |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94062614 | <b>RC (IN)</b> | 140.2           |
| <b>SW (IN)</b>  | 15.0     | <b>RIM REC</b> | W 12            |
| <b>OD (IN)</b>  | 46.9     | <b>RIM ALT</b> | W 11 ; W 13     |
| <b>SLR (IN)</b> | 21.2     | <b>ECE</b>     | E11-106R-005767 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>40</b>   | 2010 | 2340 | 2660 | 2990 | 3320 | 3640 |
| <b>30</b>   | 2110 | 2460 | 2800 | 3140 | 3480 | 3820 |
| <b>25</b>   | 2200 | 2560 | 2920 | 3270 | 3640 | 3990 |
| <b>20</b>   | 2300 | 2690 | 3060 | 3440 | 3810 | 4190 |
| <b>5 LT</b> | 2690 | 3130 | 3570 | 4010 | 4450 | 4880 |
| <b>5 HT</b> | 2300 | 2690 | 3060 | 3440 | 3810 | 4190 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.