


AW 711

| | |
|---------------------|--|
| TYRE SIZE | 400/60 R 18 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HAY HARVESTER / IMPLEMENT MACHINERY / IMPLEMENTS |
| VERSION | STUBBLE RESISTANT |
| TYRE TYPE | TL |
| LI/SS | 159 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 394 | RIM REC | 14 |
| OD (MM) | 945 | RIM ALT | 13 |
| SLR (MM) | 419 | ECE | E4-106R-001397 |
| RC (MM) | 2807 | SRI | 450 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 3.8 | 4.0 | 5.0 | 5.5 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1220 | 1585 | 1950 | 2235 | 2600 | 2965 | 3165 | 3490 | 3655 | 3815 | 4057 | 4375 |
| 40 | 1220 | 1585 | 1950 | 2235 | 2600 | 2965 | 3165 | 3490 | 3655 | 3815 | 4057 | 4375 |
| 30 | 1365 | 1775 | 2185 | 2500 | 2910 | 3320 | 3550 | 3910 | 4095 | 4275 | 4545 | 4900 |
| 25 | 1450 | 1885 | 2320 | 2660 | 3095 | 3530 | 3770 | 4155 | 4350 | 4545 | 4830 | 5210 |
| 20 | 1535 | 1995 | 2460 | 2815 | 3275 | 3735 | 3990 | 4400 | 4605 | 4810 | 5115 | 5515 |
| 10 | 1705 | 2220 | 2730 | 3125 | 3640 | 4150 | 4435 | 4885 | 5115 | 5340 | 5680 | 6125 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.