


AGRIMAX V-FLECTO



TIRE SIZE	VF 650/65 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	169 D

DIMENSIONES US STANDARD

CÓDIGO USA	94059102	RC (IN)	212.1
SW (IN)	25.6	RIM REC	DW 23 B
OD (IN)	71.3	RIM ALT	DW 21 B
SLR (IN)	31.4	ECE	E11-106R-005022

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	6500	7670	8720	9770	10690	11630
FROM 40 TO 25	7150	8430	9590	10740	11760	12800
20	7290	8600	9780	10950	11990	13040
12	7430	8760	9960	11150	12220	13290
5	7860	9270	10550	11810	12930	14060
*UPTO 5 CYC WITH FRONT LOADER	10010	11810	13430	15020	16460	17900
5 HT	7290	8600	9780	10950	11990	13040

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.