


AGRIMAX FORCE

IF 750/75 R 46

| | |
|--------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BIÇERDÖVER / YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 186 D |



UNDEFINED IS STANDARD

| | | | |
|----------|------|----------|-----------------|
| SW (MM) | 742 | RIM REC | DW 25 B |
| OD (MM) | 2294 | ECE | E11-106R-006491 |
| SLR (MM) | 1032 | SRI | 1075 |
| RC (MM) | 6802 | TRA CODE | R1W |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|---------------|------|------|-------|-------|-------|-------|-------|-------|
| 70 | 4060 | 4665 | 5355 | 6050 | 6740 | 7430 | 8125 | 8645 |
| FROM 65 TO 40 | 4465 | 5130 | 5890 | 6650 | 7410 | 8170 | 8930 | 9500 |
| 30 | 4640 | 5335 | 6125 | 6915 | 7705 | 8495 | 9285 | 9880 |
| 20 | 4820 | 5540 | 6360 | 7180 | 8000 | 8820 | 9640 | 10260 |
| 10 | 5670 | 6515 | 7480 | 8445 | 9410 | 10370 | 11340 | 12065 |
| UPTO 30 CYC | 5800 | 6665 | 7655 | 8645 | 9630 | 10620 | 11605 | 12350 |
| UPTO 15 CYC | 6920 | 7950 | 9125 | 10305 | 11485 | 12660 | 13840 | 14725 |
| UPTO 10 CYC | 7590 | 8720 | 10010 | 11305 | 12595 | 13885 | 15180 | 16150 |
| 10HT | 4640 | 5335 | 6125 | 6915 | 7705 | 8495 | 9285 | 9880 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.