


FL 630 ULTRA

| | |
|---------------------|--|
| TIRE SIZE | 800/45 R 26.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPREADER / TANKER / TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 174 D ; 184 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 828 | RIM REC | AG 28.00 |
| OD (MM) | 1393 | RIM ALT | AG 24.00 |
| SLR (MM) | 618 | ECE | E11-106R-004074 |
| RC (MM) | 4238 | SRI | 675 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|-------|-------|-------|
| 70 | 1955 | 2230 | 2505 | 3115 | 3540 | 4090 | 4640 | 5065 | 5555 | 6100 |
| 65 | 2145 | 2450 | 2750 | 3420 | 3890 | 4490 | 5095 | 5565 | 6100 | 6700 |
| 50 | 2600 | 2965 | 3330 | 4140 | 4705 | 5435 | 6165 | 6735 | 7385 | 8110 |
| 40 | 2880 | 3285 | 3690 | 4590 | 5220 | 6030 | 6840 | 7470 | 8190 | 9000 |
| 30 | 3240 | 3695 | 4150 | 5165 | 5870 | 6785 | 7695 | 8400 | 9210 | 10120 |
| 25 | 3390 | 3870 | 4345 | 5405 | 6145 | 7100 | 8050 | 8790 | 9640 | 10590 |
| 10 | 3860 | 4405 | 4945 | 6155 | 6995 | 8085 | 9170 | 10010 | 10975 | 12060 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.