

AGRIMAX RT 765

TIRE SIZE	650/75 R 42
UM	US STANDARD
MACHINERY	FELDSPRITZE / TRACTOR / TRAUBENERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	170 D



ABMESSUNGEN US STANDARD

USA-CODE	94065493	RIM ALT	DW20B;DW23B
SW (IN)	25.8	ECE	E11-106R-006402
OD (IN)	80.4	TRA CODE	R1W
SLR (IN)	36.1	TREAD DEPTH (32nd)	73.08
RC (IN)	242.0	TMPH (TM/H)	0
RIM REC	DW21B		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	6220	7140	8200	9260	10320	11380	12430	13230
30	6540	7510	8620	9720	10840	11950	13060	13890
25	6810	7830	8980	10140	11300	12470	13620	14480
15	7150	8220	9440	10650	11870	13080	14310	15210
5 LT	8330	9580	10990	12410	13830	15240	16670	17720
5 HT	7150	8220	9440	10650	11870	13080	14310	15210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.