

LOADER PLUS



LOADER PLUS

LOADER PLUS (L-3) is a bias-ply tyre specially designed for loaders. The tread compound provides cut-and-chip-resistant properties and suites best for loading and dozing operations.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø25"	29.5 - 25	TL	L3	28	-	25.00/3.5	-	0	760	1860	849	5544	39	STD
	23.5 - 25	TT	L3	16	-	19.50/2.5	-	0	610	1640	749	4855	32,5	STD
	20.5 - 25	TT	L3	20	-	17.00/2.0	-	0	540	1490	685	4410	29,5	STD
	14.00 - 25	TT	L3	20	-	10.00/1.5	-	0	375	1368	630	4050	26,5	STD

STD: STANDARD, DB: DUAL BEAD

TECHNOLOGIES	PERFORMANCES
  L3	 

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 16/09/2026

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
17.5 - 25	TT	L3	20	-	14.00/1.5	-	0	440	1345	622	3980	26,5	DB
20.5 - 25	TT	L3	16	-	17.00/2.0	-	0	540	1490	685	4410	29,5	STD
17.5 - 25	TT	L3	16	-	14.00/1.5	-	0	440	1345	622	3980	26,5	STD
29.5 - 25	TL	L3	32	-	25.00/3.5	-	0	760	1860	849	5544	39	STD
23.5 - 25	TL	L3	24	-	19.50/2.5	-	0	610	1640	749	4855	32,5	STD
23.5 - 25	TL	L3	16	-	19.50/2.5	-	0	610	1640	749	4855	32,5	STD
20.5 - 25	TL	L3	16	-	17.00/2.0	-	0	540	1490	685	4410	29,5	STD
26.5 - 25	TL	L3	32	-	22.00/3.0	-	0	680	1740	796	5150	36,5	STD
20.5 - 25	TL	L3	20	-	17.00/2.0	-	0	540	1490	685	4410	29,5	STD

STD: STANDARD, DB: DUAL BEAD

TECHNOLOGIES	PERFORMANCES
  L3   -	 

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 16/09/2026

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
23.5 - 25	TT	L3	20	-	19.50/2.5	-	0	610	1640	749	4855	32,5	STD
23.5 - 25	TL	L3	20	-	19.50/2.5	-	0	610	1640	749	4855	32,5	STD
26.5 - 25	TL	L3	28	-	22.00/3.0	-	0	680	1740	796	5150	36,5	STD

STD: STANDARD, DB: DUAL BEAD



TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baktishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 16/09/2026