

AGRIMAX V- FLECTO

VF 710/70 R 42

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
VERSION	STEEL BELTED
TIRE TYPE	TL
	193 D



UNDEFINED US STANDARD

USA CODE	94075140	RC (IN)	245.4
SW (IN)	28.3	RIM REC	DW 25 B
OD (IN)	81.0	RIM ALT	DW 23 B; DW 24 B
SLR (IN)	36.5	ECE	E11-106R-0010960

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52
45	8540	9920	11310	12930	14310	15700	17310	18230	20070	21690	23070
FROM 40 TO 25	9380	10900	12420	14200	15720	17240	19010	20030	22060	23830	25350
20	9580	11120	12680	14480	16040	17590	19400	20440	22510	24320	25860
12	9770	11340	12930	14770	16360	17930	19770	20830	22950	24790	26370
5	10330	11990	13670	15620	17290	18970	20920	22030	24270	26220	27890
*UPTO 5 CYC WITH FRONT LOADER	13140	15270	17390	19880	22010	24140	26620	28040	30890	33370	35490
5 HT	9580	11120	12680	14480	16040	17590	19400	20440	22510	24320	25860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.