

# TF 9090

|                     |                                   |
|---------------------|-----------------------------------|
| <b>TIRE SIZE</b>    | 10.00 - 16                        |
| <b>UM</b>           | IS STANDARD                       |
| <b>CONSTRUCTION</b> | BIAS                              |
| <b>MACHINERY</b>    | SMALL TRACTOR / TRACTOR / TRAILER |
| <b>VERSION</b>      | SPECIAL                           |
| <b>TIRE TYPE</b>    | TT                                |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 275  | <b>RIM REC</b> | W 8             |
| <b>OD (MM)</b>  | 900  | <b>RIM ALT</b> | W 8 L           |
| <b>SLR (MM)</b> | 409  | <b>ECE</b>     | E11-106R-004418 |
| <b>RC (MM)</b>  | 2714 | <b>PR</b>      | 10              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.40</b> |
| 30                | 1360        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.