


AGRIMAX FORCE

TIRE SIZE	IF 650/65 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	161 D



DIMENSIUNI US STANDARD

USA CODE	94060054	RC (IN)	199.9
SW (IN)	25.6	RIM REC	DW 23 B
OD (IN)	67.3	RIM ALT	DW 20 B
SLR (IN)	30.1	ECE	E4-106R-001826

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	5190	6120	6940	7790	8530	9270
FROM 40 TO 25	5710	6720	7640	8560	9380	10200
20	5930	6990	7940	8910	9750	10600
12	6160	725	8240	9250	10130	11010
5	7240	8530	9700	10870	11900	12940
UPTO 20 CYC	7420	8740	9920	11120	12190	13250
UPTO 10 CYC	8840	10420	11840	13270	14540	15800
UPTO 5 CYC	9700	11430	12980	14550	15940	17330
5HT	5930	6990	7940	8910	9750	10600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.