

AGRIMAX RT 855



AGRIMAX RT 855
RADIAL TRACTOR TIRES

AGRIMAX RT 855



AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.



SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
Ø16"	210/95 R 16 (7.50 R 16)			W 7 W 6 6 LB	8.4	31.7	14.2	94.0	370	STD
	180/95 R 16 (6.50 R 16)			5.5 F 6.0 F	7.3	29.9	13.4	89.2	350	STD
	210/95 R 16 (7.50 R 16)		116 A8	W 7 W 6 6 LB	8.4	31.7	13.8	92.6	370	IMP
Ø18"	210/95 R 18 (7.50 R 18)			W 7 W 6	8.4	33.7	15.2	101.0	400	STD
	250/80 R 18			W 8 W 7 W 9	9.8	32.9	14.8	100.0	410	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
	R1W		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index
	176 lbs		

SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
210/95 R 18 (7.50 R 18)		122 A8	W 7	W 6	8.4	33.7	14.9	101.0	400	IMP
Ø20"	280/85 R 20 (11.2 R 20)		W 10	W 9	11.5	38.7	17.6	117.2	475	STD
	250/85 R 20 (9.5 R 20)		W 8	W 7 W 9	9.8	37.0	16.7	110.7	450	STD
	210/95 R 20 (7.50 R 20)		W 7	W 6	8.4	35.7	16.5	108.2	425	STD
	280/85 R 20 (11.2 R 20)		W 10	W 9	11.5	38.7	17.4	116.2	475	STD
	320/85 R 20 (12.4 R 20)		W 11	W 9 W 10	13.0	41.4	18.4	122.0	500	STD
	210/90 R 20 (8.3 R 20)		W 7	W 6	8.3	35.0	16.2	105.6	425	STD
Ø22"	250/85 R 22 (9.5 R 22)		W 8	W 7	9.9	38.8	17.8	116.7	475	STD
	250/85 R 22		W 8	W 7	9.9	38.8	17.8	116.7	475	SPL
Ø24"	250/85 R 24 (9.5 R 24)		W 8	W 7 W 9	9.9	40.8	18.7	122.2	500	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index
			

SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
340/85 R 24 (13.6 R 24)			W 12	W 11	13.9	46.8	20.9	139.4	575	STD
420/85 R 24 (16.9 R 24)			W 15 L	W 14 L W 13	17.7	52.1	22.9	153.5	625	SPL
420/85 R 24 (16.9 R 24)			W 15 L	W 14 L W 13	17.7	52.1	23.2	153.9	625	STD
280/85 R 24 (11.2 R 24)			W 10	W 9	11.5	42.8	19.4	126.9	525	SPL
320/85 R 24 (12.4 R 24)			W 11	W 9 W 10	13.0	45.4	20.4	134.8	550	STD
380/85 R 24 (14.9 R 24)			W 12	W 11 W 13	15.0	49.4	21.8	146.5	600	SPL
340/85 R 24 (13.6 R 24)			W 12	W 11	13.9	46.8	20.9	139.4	575	SPL
280/85 R 24 (11.2 R 24)			W 10	W 9	11.5	42.8	19.4	126.9	525	STD
380/85 R 24 (14.9 R 24)			W 12	W 11 W 13	15.0	49.4	21.8	146.5	600	STD
320/85 R 24 (12.4 R 24)			W 11	W 9 W 10	13.0	45.4	20.4	134.8	550	SPL

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index
			

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baikrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
250/85 R 24 (9.5 R 24)			W 8	W 7 W 9	9.9	40.8	18.7	122.2	500	SPL
Ø28"			W 8	W 7 W 9	9.9	44.8	20.4	134.7	550	SPL
			W 15 L	W 13 W 14 L	17.2	56.1	25.1	167.0	675	STD
			W 12	W 11	13.9	51.8	23.7	156.0	625	STD
			W 12	W 11 W 13	15.0	53.4	23.9	158.1	650	SPL
			W 11	W 9 W 10	13.0	49.4	22.4	147.4	600	STD
			W 12	W 11 W 13	15.0	53.4	23.9	158.1	650	STD
			W 12	W 11	13.9	50.7	23.1	153.1	625	STD
			W 15 L	W 13 W 14 L	17.2	56.1	25.1	167.0	675	SPL
			W 10	W 9	11.5	46.7	21.5	140.1	575	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index
			

SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
340/85 R 28 (13.6 R 28)			W 12	W 11	13.9	50.7	23.1	153.1	625	SPL
320/85 R 28 (12.4 R 28)			W 11	W 9 W 10	13.0	49.4	22.4	147.4	600	SPL
250/85 R 28 (9.5 R 28)			W 8	W 7 W 9	9.9	44.8	20.4	134.7	550	STD
280/85 R 28 (11.2 R 28)			W 10	W 9	11.5	46.7	21.5	140.1	575	SPL
Ø30"										
			W 16 L	W 14 L W 15 L	18.7	60.8	26.8	179.6	725	SPL
			W 16 L	W 14 L W 15 L	18.7	60.8	26.8	179.6	725	STD
			W 15 L	W 13 W 14 L	17.2	58.1	26.0	174.1	700	SPL
			W 12	W 11 W 13	15.0	55.4	24.9	165.0	675	SPL
			W 12	W 11 W 13	15.0	55.4	24.9	165.0	675	STD
			W 15 L	W 13 W 14 L	17.2	58.1	26.0	174.1	700	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
	R1W		D
	176 lbs		176 lbs
			
		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	

	SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
				REC RIM	ALT RIM						
		DW	FR								
Ø32"	320/85 R 32 (12.4 R 32)			W 11	W 9 W 10	13.0	53.4	24.4	160.7	650	STD
	320/85 R 32 (12.4 R 32)			W 11	W 9 W 10	13.0	53.4	24.4	160.7	650	SPL
Ø34"	380/85 R 34 (14.9 R 34)			W 12	W 11 W 13	15.0	59.4	26.9	177.3	725	STD
	380/85 R 34 (14.9 R 34)			W 12	W 11 W 13	15.0	59.4	26.9	177.3	725	SPL
	420/85 R 34 (16.9 R 34)			W 15 L	W 13 W 14 L	17.2	62.1	27.9	185.1	750	STD
	320/85 R 34 (12.4 R 34)			W 11	W 9 W 10	13.0	55.4	25.4	168.5	675	SPL
	420/85 R 34 (16.9 R 34)			W 15 L	W 13 W 14 L	17.2	62.1	27.9	185.1	750	SPL
	460/85 R 34 (18.4 R 34)			W 16 L	W 14 L W 15 L	18.7	64.8	28.4	191.5	775	SPL
	320/85 R 34 (12.4 R 34)			W 11	W 9 W 10	13.0	55.4	25.4	168.5	675	STD
	460/85 R 34 (18.4 R 34)			W 16 L	W 14 L W 15 L	18.7	64.8	28.4	191.5	775	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
	R1W		176 lbs
		 Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	

SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
460/85 R 34 (18.4 R 34)			W 16 L	W 14 L W 15 L	18.7	64.8	28.4	191.5	775	STD
420/85 R 34 (16.9 R 34)			W 15 L	W 13 W 14 L	17.2	62.1	28.7	188.3	750	STD
Ø36"	320/85 R 36 (12.4 R 36)		W 11	W 9 W 10	13.0	57.4	26.5	173.4	700	SPL
	340/85 R 36 (13.6 R 36)		W 12	W 11	13.9	58.7	27.1	177.4	725	SPL
	340/85 R 36 (13.6 R 36)		W 12	W 11	13.9	58.7	27.1	177.4	725	STD
	320/85 R 36		W 11	W 9 W 10	13.0	57.4	26.5	173.4	700	STD
	320/85 R 36 (12.4 R 36)		W 11	W 9 W 10	13.0	57.4	26.5	173.4	700	STD
Ø38"	320/85 R 38 (12.4 R 38)		W 11	W 9 W 10 DW 10 DW 11	13.0	59.4	27.6	180.3	725	STD
	520/85 R 38 (20.8 R 38)		DW 16 L	DW 18 L DD 16 L	20.3	72.8	32.0	215.2	875	STD
	520/85 R 38 (20.8 R 38)		DW 16 L	DW 18 L DD 16 L	20.3	72.8	33.3	220.3	875	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index
			

SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
380/85 R 38 (14.9 R 38)			W 12	W 11 W 13	15.0	63.4	29.0	190.6	775	SPL
420/85 R 38 (16.9 R 38)			W 15 L	W 13 W 14 L	17.2	66.1	30.0	197.4	800	STD
340/85 R 38 (13.6 R 38)			W 12	W 11	13.9	60.7	28.0	183.8	750	SPL
480/80 R 38 (18.4 R 38)			DW 16 L	W 14 L W 15 L	18.7	68.8	30.9	203.2	825	STD
460/85 R 38 (18.4 R 38)			W 16 L	W 14 L W 15 L	18.7	68.8	30.9	204.9	825	SPL
380/85 R 38 (14.9 R 38)			W 12	W 11 W 13	15.0	63.4	29.0	190.6	775	STD
420/85 R 38 (16.9 R 38)			W 15 L	W 13 W 14 L	17.2	66.1	30.0	197.4	800	SPL
520/85 R 38			DW 16 L	DW 18 L DD 16 L	20.3	72.8	33.3	220.3	875	SPL
460/85 R 38 (18.4 R 38)			W 16 L	W 14 L W 15 L	18.7	68.8	30.9	204.9	825	STD
520/85 R 38 (20.8 R 38)			DW 16 L	DW 18 L DD 16 L	20.3	72.8	32.0	215.2	875	SPL

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index
			

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baikrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
320/85 R 38 (12.4 R 38)			W 11	W 9 W 10 DW 10	13.0	59.4	27.6	180.3	725	SPL
340/85 R 38 (13.6 R 38)			W 12	W 11	13.9	60.7	28.0	183.8	750	STD
Ø42"	520/85 R 42 (20.8 R 42)		DW 16 L W 16 A DD 16	DW 18 A DD 18 W 18 A DD 18 L	21.26	76.8	35.23	233	925	SPL
	520/85 R 42 (20.8 R 42)		DW 16 L W 16 A DD 16	DW 18 A DD 18 W 18 A DD 18 L	20.3	76.8	33.8	227.6	925	SPL
	520/85 R 42 (20.8 R 42)		DW 16 L W 16 A DD 16	DW 18 A DD 18 W 18 A DD 18 L	20.3	76.8	33.8	227.6	925	STD
	520/85 R 42 (20.8 R 42)		DW 16 L W 16 A DD 16	DW 18 A DD 18 W 18 A DD 18 L	21.26	76.8	35.23	233	925	STD
	480/80 R 42 (18.4 R 42)		W 16 A DD 16 DW 16 A	DD 16 L DW 16 L W 16 L	18.9	72.2	32.9	216.3	875	STD
Ø46"	420/80 R 46 (16.9 R 46)		W 13	W 12	16.5	72.4	34.0	222.1	900	STD
	520/85 R 46 (20.8 R 46)		DW 16 L W 16 A W 16 L DD 16	DW 18 L W 18 L W 18 A	20.3	80.8	36.6	242.4	975	STD
	480/80 R 46 (18.4 R 46)		DW 16 A W 16 A DD 16	W 16 L DD 16 L DW 16 L	18.9	76.2	35.2	231.1	925	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index
			

SIZE	LI/SS		RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
420/80 R 46 (16.9 R 46)			W 13	W 12	16.5	72.4	34.0	222.1	900	STD
480/80 R 46 (18.4 R 46)			DW 16 A W 16 A DD 16	W 16 L DD 16 L DW 16 L	18.9	76.2	35.2	231.1	925	STD
520/85 R 46 (20.8 R 46)			DW 16 L W 16 A W 16 L DD 16	DW 18 L W 18 L W 18 A	20.3	81.7	38.0	248.4	975	STD
420/80 R 46 (16.9 R 46)			W 13	W 12	16.5	72.4	34.0	222.1	900	SPL
520/85 R 46			DW 16 L W 16 A W 16 L DD 16	DW 18 L W 18 L W 18 A	20.3	80.8	36.6	242.4	975	SPL
Ø50"	480/80 R 50 (18.4 R 50)		DW 16 L	DW 15 L W 15 L	19.3	80.2	37.0	243.4	975	STD
	520/85 R 50 (20.8 R 50)		DW 16L	DW 18 L	20.3	84.8	39.1	254.8	1025	STD
	420/80 R 50 (16.9 R 50)		W 13	W 12	16.5	76.8	36.0	234.4	950	SB
	480/80 R 50 (18.4 R 50)		DW 16 L	DW 15 L W 15 L	19.3	80.2	37.2	243.4	975	SB

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
	R1W		176 lbs
			
		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	