


# AW 09

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>380/55 - 17</b>  |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       |  BIAS  |
| <b>MACHINERY</b>          | СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ / ПРИЦЕП /<br>ПРЕСС-ПОДБОРЩИК / КОМБАЙН<br>/ КОМБАЙН /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 125 A8  |
| <b>LI/SS FREE ROLLING</b> | 138 A8  |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94038077 | <b>RC (IN)</b> | 98.1           |
| <b>SW (IN)</b>  | 15.4     | <b>RIM REC</b> | 13.00          |
| <b>OD (IN)</b>  | 33.5     | <b>ECE</b>     | E4-106R-000379 |
| <b>SLR (IN)</b> | 14.8     |                |                |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 41   |
|-----------|------|
| 5 FR      | 7290 |
| 15 FR     | 6190 |
| 20 FR     | 5830 |
| 25 FR     | 5200 |
| 5 DW      | 5090 |
| 15 DW     | 4330 |
| 20 DW     | 4080 |
| 25 DW     | 3640 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.