

# AGRIMAX RT 855

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>250/85 R 28</b>                                                                       |
| <b>UM</b>           | IS STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS                    |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TL/TT</b>        | TL                                                                                       |
| <b>LI/SS</b>        | 112 A8/B                                                                                 |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 251  | <b>RIM REC</b> | W 8            |
| <b>OD (MM)</b>  | 1137 | <b>RIM ALT</b> | W 7 ; W 9      |
| <b>SLR (MM)</b> | 519  | <b>ECE</b>     | E4-106R-000646 |
| <b>RC (MM)</b>  | 3421 | <b>SRI</b>     | 550            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6 | 0.8 | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------|-----|-----|------|------|------|------|
| <b>50</b>    | 620 | 720 | 820  | 920  | 1020 | 1120 |
| <b>40</b>    | 620 | 720 | 820  | 920  | 1020 | 1120 |
| <b>30</b>    | 660 | 770 | 880  | 985  | 1095 | 1200 |
| <b>10 LT</b> | 830 | 965 | 1100 | 1235 | 1370 | 1505 |
| <b>10 HT</b> | 660 | 770 | 880  | 985  | 1095 | 1200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.