


AW 711

| | |
|---------------------|---|
| TIRE SIZE | VF 410/50 R 16.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 153 B |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94055814 | RC (IN) | 98.9 |
| SW (IN) | 16.1 | RIM REC | AG 13.00 |
| OD (IN) | 32.9 | ECE | E11-106R-005024 |
| SLR (IN) | 13.8 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 67 |
|-------------------------|------|------|------|------|------|------|------|------|------|------|
| FROM 5 TO 30 MPH | 2260 | 2970 | 3590 | 4170 | 4790 | 5430 | 5850 | 6420 | 7040 | 8050 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.