


# MP 567

<b>TIRE SIZE</b>	<b>11.5/80 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ATTREZZI AGRICOLI / SOLLEVATORE TELESCOPICO / ATTREZZI AGRICOLI / SOLLEVATORE TELESCOPICO / VEICOLO UNIVERSALE
<b>VERSIONE</b>	IMPLEMENT
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	119 A8
<b>LI/SS FREE ROLLING</b>	131 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	292	<b>RIM REC</b>	9.0
<b>OD (MM)</b>	868	<b>ECE</b>	E11-106R-003529
<b>SLR (MM)</b>	393	<b>PR</b>	10
<b>RC (MM)</b>	2578		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.40</b>
<b>40 FR</b>	1950
<b>40 DW</b>	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.