


AGRIMAX V- FLECTO

VF 710/55 R 38

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
VERSION	STANDARD
TIRE TYPE	TL
	175 D



UNDEFINED US STANDARD

USA CODE	94067107	RC (IN)	206.4
SW (IN)	28.0	RIM REC	DW 25 B
OD (IN)	68.9	RIM ALT	DW 24 B
SLR (IN)	30.7	ECE	E11-106R-006844

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	6370	7340	8440	9410	10520	11490	12870	13830
FROM 40 TO 25	7000	8070	9280	10350	11560	12630	14150	15210
20	7140	8220	9470	10550	11790	12870	14430	15510
12	7290	8390	9660	10760	12030	13140	14720	15820
5	7700	8870	10210	11390	12720	13890	15560	16730
*UPTO 5 CYC WITH FRONT LOADER	9800	11290	13000	14480	16190	17680	19810	21300
5 HT	7140	8220	9470	10550	11790	12870	14430	15510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.