


# AGRIMAX SIRIO

<b>TIRE SIZE</b>	<b>540/65 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	HIGH SPEED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	150 D ; 147 E



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94045310	<b>RC (IN)</b>	173.2
<b>SW (IN)</b>	20.9	<b>RIM REC</b>	W 16 L
<b>OD (IN)</b>	57.6	<b>RIM ALT</b>	W 18
<b>SLR (IN)</b>	26.3	<b>ECE</b>	E4-106R-000814

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	3200	3670	4210	4750	5290	5830	6300	6780
40	3470	3990	4590	5170	5760	6360	6880	7390
30	3650	4200	4820	5430	6060	6680	7220	7760
25	3800	4380	5030	5670	6320	6970	7530	8090
15	4120	4730	5430	6130	6830	7530	8150	8750
5	5210	5990	6880	7760	8640	9530	10310	11080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.